

PowerWalker DP-522

SNMP Module

Monitor UPS through RJ45 network connection

RJ45 10/100BaseT port

Protocol support SNMP-V1

Supported MIB: RFC1628 and PPC MIB

Compatible with all UPS which have RS-232 port



Item-No. 10120503

PowerWalker DP-522 module is a communication solution for UPS monitoring and control. This SNMP module allows remote monitor and manage multiple UPSs from anywhere with internet access. Integrated web access will leverage internet capability of DP-522 module to remotely program or shut down UPSs. Equipped with DP-522, power conditions of all UPSs can be monitored anytime/anywhere even though the UPS units are located in different floors. Besides, this card also come equipped with easy-to-update firmware feature. Whenever the updated firmware is released, system manager can download it and simply upgrade all with one click.

Product Features

- Allows to control and monitoring of multiple UPSs through RJ45 network connection
- Real-time dynamic graphs of UPS data (voltage, frequency, load level, battery level)
- Warning notifications via audible alarm, broadcast, mobile messenger, e-mail and SNMP traps
- Historic data log
- Simple firmware upgrade with one click
- Password security protection and remote access management
- Compatible with all UPS which have RS-232 port

Supports following models:

Compatible with all UPS which have RS-232 port



Technical Details

Product Features

СРИ	ARM 50Mhz 32bit
System Clock	25Mhz
Flash memory	1 MB
SDRAM	8 MB
LED	6
Watch Dog	YES
SNMP Protocol	V1
Supported MIB	RFC1628 & PPC MIB
LAN Interface	
Туре	10M/100M UTP
Function	SNMP, Web server
Ethernet Throughput	808 Kb/sec
Latency	0.89 milliseconds
Power Specifications	
DC Input Voltage	+4.8V ~ +7V
DC Input Current	250mA
Software & System Requirements	
Port	1x RJ45
Port Product Details	1x RJ45
	1x RJ45 48 x 63 x 21 mm
Product Details	
Product Details Dimensions	48 x 63 x 21 mm
Product Details Dimensions Colour	48 x 63 x 21 mm Black
Product Details Dimensions Colour Weight	48 x 63 x 21 mm Black 70g
Product Details Dimensions Colour Weight Model Code	48 x 63 x 21 mm Black 70g
Product Details Dimensions Colour Weight Model Code Environment	48 x 63 x 21 mm Black 70g DP-522
Product Details Dimensions Colour Weight Model Code Environment Temperature	48 x 63 x 21 mm Black 70g DP-522 0°C - 60°C 5 - 95% RH (non- condensing)
Product Details Dimensions Colour Weight Model Code Environment Temperature Humidity	48 x 63 x 21 mm Black 70g DP-522 0°C - 60°C 5 - 95% RH (non- condensing)
Product Details Dimensions Colour Weight Model Code Environment Temperature Humidity Package Conter	48 x 63 x 21 mm Black 70g DP-522 0°C - 60°C 5 - 95% RH (non- condensing) nt DP-522 module, Power Adapter,
Product Details Dimensions Colour Weight Model Code Environment Temperature Humidity Package Contert	48 x 63 x 21 mm Black 70g DP-522 0°C - 60°C 5 - 95% RH (non- condensing) nt DP-522 module, Power Adapter,
Product Details Dimensions Colour Weight Model Code Environment Temperature Humidity Package Conter Package Content Logistic Data	48 x 63 x 21 mm Black 70g DP-522 0°C – 60°C 5 - 95% RH (non- condensing) nt DP-522 module, Power Adapter, Software CD, manual
Product Details Dimensions Colour Weight Model Code Environment Temperature Humidity Package Conter Package Content Logistic Data Giftbox Language	48 x 63 x 21 mm Black 70g DP-522 0°C - 60°C 5 - 95% RH (non- condensing) nt DP-522 module, Power Adapter, Software CD, manual
Product Details Dimensions Colour Weight Model Code Environment Temperature Humidity Package Conter Package Content Logistic Data Giftbox Language Manual Language	48 x 63 x 21 mm Black 70g DP-522 0°C – 60°C 5 - 95% RH (non- condensing) at DP-522 module, Power Adapter, Software CD, manual EN EN

Version: EN 02/05/2012

We reserve the right for technical changes and mistakes